



NOTES:

ELECTRICAL:

- | | |
|--------------------------|------------------------------------|
| 1. VOLTAGE RATING | : 125 VAC RMS. |
| 2. CURRENT RATING | : 1.5 AMP. |
| 3. CONTACT RESISTANCE | : 30 MILLIOHMS MAX |
| 4. INSULATION RESISTANCE | : 500 MEGOHMS MIN @ 500 NDC. |
| 5. DIELECTRIC STRENGTH | : 1000 VAC RMS 50Hz or 60Hz, 1MIN. |

MECHANICAL:

1. HOUSING & INSERT MATERIAL. : PBT : P666 UJ94V-0.
2. CONTACT MATERIAL. : DIAMETER0.45MM PHOSPHOR BRONZE GOLD PLATING OVER NICKEL.
3. SHIELD : 0.20~0.25MM THICKNESS BRASS WITH TIN PLATED.
4. MATING/UNMATING FORCE : 2.2KG. F MAX.
5. RETENTION STRENGTH : 7.7KG. F MIN BETWEEN JACK AND PLUG.
6. OPERATING LIFE : 600 CYCLES MIN.
- ENVIRONMENTAL:
1. STORAGE : -10°C ~+40°C RELATIVE HUMIDITY<70%
2. OPERATION : -40°C ~+70°C

A	JIONS-R445-0005		2010/03/18
REV	ECN NO	DESCRIPTION	DATE

Jions 北京玖思启明电子科技有限公司

X. ±0.30	APPO:	Mr. Wu	TITLE:
X. ±0.20			
.XX ±0.10	CHKO:	Mr. Wu	2*1 25. 3H RJ45 带屏蔽
.XXX±0.05			
X' ±2"	DR:	Gus chng	PART NO:
X' ±1"			JTIONS-0014

UNITS:
mm

SCALE:
1:1

客户图
DWG NO:
www.jions.com.cn

SHEET:	
REV:	