



RECOMMEND PCB LAYOUT
TOLERANCE: ±0.05
TOP VIEW

MATERIALS

1. HOUSING: THERMOPLASTIC (UL 94V-0).
2. COVER: THERMOPLASTIC (UL 94V-0).
3. TERMINAL: COPPER ALLOY.
GOLD PLATED ON CONTACT AREA,
TIN PLATED ON SOLDER TAILS,
NICKEL UNDER PLATED OVERALL.
4. BOARD LOCK: SPCC, TIN PLATED OVER NICKEL.
5. SHELL: SPCC, NICKEL PLATED OVERALL.
6. RIVET: Zn ALLOY, NICKEL PLATED OVERALL.

SPECIFICATION

1. MATING FORCE: 4.5KG/MAX.
2. UNMATING FORCE: 1.0-4.0KG.
3. DIELECTRIC WITHSTANDING VOLTAGE:
500V AC R.M.S. FOR ONE MINUTE.
4. INSULATION RESISTANCE:
1000MΩ MIN AT 500V DC.
5. CONTACT RESISTANCE: 30mΩ MAX.
6. OPERATING TEMPERATURE : -25°C TO +85°C.

REV A	JIONS-DVI-0001	DESCRIPTION	2011/02/01	DATE											
ECN NO															

Jions 北京玖恩启明电子科技有限公司

X. ±0.30	APPD: Mr.wu	TITLE: DVI 24PIN FEMALE
XX ±0.20	CHKD: Mr.wu	
XXX±0.05	Dr: Gus chong	
X' ±1'	PART NO: JIONS-0028	
UNITS: mm	SCALE: 1:1	DWG NO: WWW.JIONS.COM.CN
		客户图 SHEET:10/1
		REV: