



RECOMMENDED PCB LAYOUT (TOP VIEW)
(ALL TOLERANCES ARE ±0.05)

- Specifications:
1. Rated Current: 1.5A
 2. Contact resistance: 40mΩ MAX.
 3. Insulation resistance: 500MΩ MIN.
 4. Dielectric withstand: 500V AC for 1 minute
 5. Operating temperature: -40°C~+80°C
 6. Insertion/Extraction life: 750 Cycles

e	LED	1	YELLOW
d	Terminal	1	GREEN
c	Cover	8	PHOSPHOR BRONZE T=0.35mm
b	Shell	1	LCP GF30% UL94V-0
a	Housing	1	BRASS T=0.20mm
NO.	PART NAME	Q'TY	MATERIAL
			PLATING & COLOR
			Remark

LED COLOR	
MODE	COLOR
LED 1 10(+) 9(-)	GREEN
LED 2 12(+) 11(-)	YELLOW

X. ±0.30	APPO: Mr.wu	TITLE: 沉板式 单口RJ45 带灯 左
.XX ±0.10	CHKD: Mr.wu	绿右黄
.XXX±0.05	DR: Gus chong	PART NO: JIONS-0047
X' ±1°		

UNITS: mm	SCALE: 1:1	DWG NO: WWW.JIONS.COM.CN	SHEET: 10/1
-----------	------------	--------------------------	-------------



客户图

REV:

REV:

Jions 北京玖思启明电子科技有限公司

A	JIONS-RJ45-0014	2012/09/19
REV	ECN NO	DESCRIPTION