



SPECIFICATIONS:

Contact current Rating:
 1.8 Amperes for pin1&pin4,
 0.25 Amperes other contacts
 Dielectric Withstanding Voltage:AC 100V(RMS)
 Insulation resistance:100Megohms Minimum.
 Contact Resistance:
 30mΩ Max for pin1&pin4
 50mΩMax for other contacts
 Mechanical Characteristics:
 Mating Force:35 Newtons,Maximum
 Unmating Force:10 Newtons,Minimum.
 MATERIAL:
 Housing: PBT+30%GF 94V-0 COLOR:BLUE
 Contact: copper alloy(T=0.25mm)
 Shell: SPCC
 PLATING:
 Contact: Au Plated on contact area
 Tin Plated on solder area
 Nickel underplating over all
 Shell: Nickel Plated
 operating Temperature:-55~10+85~

REV	ECN NO	DESCRIPTION	DATE
A	JIONS-USB-0008		2012/04/11

JIONS 北京玖思启明电子科技有限公司

X	±0.30	APPD	Mr.WU	TITLE
.X	±0.20			3.0 简体 USB A 公 单边铁
.XX	±0.10	CHKD	Mr.WU	壳脚
.XXX	±0.05			
X'	±2"	DR		PART NO: JIONS-0050
X'	±1"		Gus chong	

UNITS	SCALE	DWG NO:	客户图	SHEET:10/1
mm	1:1	WWW.JIONS.COM.CN		REV: