



规格

导体芯数	N	24	
间距	P	0.5	±0.05
总长度	TL	60	±2.0
全间距	PT	11.5	±0.08
边距	M	0.5	±0.08
总宽度	W	12.5	±0.08
线口长度	S1	4.0	±0.5
	S2	4.0	±0.5
补强板长度	B1	6.0	±1.0
	B2	6.0	±1.0
插接厚度	T	0.303	±0.03
线身厚度	Tt	0.121	±0.03
切断斜度	A	≤0.3	

特殊要求
1、Storage condition(储存条件):
Temp:15° C~25° C(温度15° C~25° C)
Humidity:30~60RH%(湿度30~60RH%);
2、产品符合:ROHS标准;
Products conform to the ROHS standard
3、镀层: 镀Sn 1um以上;
Plating: plating Sn 1um above

REV	JIONS-FPC-0002	DESCRIPTION	2015/03/31	DATE
ECN NO				

JIONS 北京玖思启明电子科技有限公司

X. ±0.30	APPD.	Mr.WU	TITLE:
X ±0.20	CHKD:	Mr.WU	异面 FPC60cm排线 24PIN 0.5
.XXX±0.05	Dr:	Gus chong	PART NO: JIONS-0060
X ±1"	UNITS:	mm	SCALE: 1:1
	DWG NO:	WWW.JIONS.COM.CN	SHEET:10/1