



LED COLOR DISPLAY

- NOTES:
- ELECTRICAL:
1. VOLTAGE RATING : 125 VAC RMS.
  2. CURRENT RATING : 1.5AMP.
  3. CONTACT RESISTANCE : 40 MILLIOHMS MAX.
  4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
  5. DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.
- MECHANICAL:
1. HOUSING MATERIAL : GLASS FILLED POLYESTER UL94V-0.
  2. CONTACT MATERIAL : PHOSPHOR BRONZE Ø0.46mm.
  3. PLATING : 1: CONTACT AREA- SELECTIVE GOLD PLATING.
  4. OPERATING LIFE PRE-SOLDER : 750 CYCLES MIN.
  5. PCB RETENTION POST-SOLDER: 1 LB MIN.
  6. PCB RETENTION POST-SOLDER: 10 LBS MIN.
- ENVIRONMENTAL:
1. STORAGE : -40°C TO +85°C.
  2. OPERATION: -40°C TO +85°C.
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

A	JIONS-RJ45-0016	2015/04/25	JIONS 北京玖思启明电子科技有限公司	X. ±0.30	APPD: Mr.wu	TITLE: 图后3.05单口带屏蔽RJ45 左
REV	ECN NO	DESCRIPTION	DATE	.XX ±0.10	CHKD: Mr.wu	绿右橙绿
1				.XXX±0.05	DR: Gus chong	PART NO: JIONS-0062 变更后
				X' ±1'	UNITS: mm	SCALE: 1:1
						DWG NO: 客户图
						WWW.jions.com.cn
						SHEET:10/1
						REV: