



NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 30 MILLIOHMS MAX
4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500 NDC.
5. DIELECTRIC STRENGTH : 1000 VAC RMS 50Hz or 60Hz, 1MIN.

MECHANICAL:

1. HOUSING & INSERT MATERIAL : PBT UL94V-0.
 2. CONTACT MATERIAL : DIAMETER 0.45MM PHOSPHOR BRONZE GOLD PLATING OVER NICKEL.
 3. SHIELD : 0.20~0.25MM THICKNESS BRASS WITH NI PLATED.
 4. MATING/UNMATING FORCE : 2.2KG. F MAX.
 5. RETENTION STRENGTH : 7.7KG. F MIN BETWEEN JACK AND PLUG.
 6. OPERATING LIFE : 600 CYCLES MIN.
- ENVIRONMENTAL:
1. STORAGE : -10°C ~+40°C REACTIVE HUMIDITY<70%
 2. OPERATION : -40°C ~+70°C

此物料有带弹片, 不带弹片, 带灯和不带灯。

REV	ECN NO	DESCRIPTION	DATE
A	JIONS-0072		2011/06/15

X.	±0.30	APPD.	Mr.wu	TITLE:
X	±0.20			单口 短体 RJ45 EMI 不带
.XX	±0.10	CHKD:	Mr.wu	灯
.XXX	±0.05			
X'	±2°	DR:	Gus chong	PART NO:
X'	±1°			JIONS-0072
UNITS:	mm	SCALE:	1:1	北京致恩启明电子科技有限公司
				SHEET:10/1
				REV: