



P. C. B. LAYOUT

#### SPECIFICATIONS

- Voltage rating: 250V AC, DC
- Current rating: 3A, AC, DC
- Withstanding Voltage: 1000V AC/minute
- Insulation resistance: 1000MΩ min
- Temperature range: -25° C +85° C
- Contact resistance: 20mΩ max

#### WAFER

- Part No. : W2501V-NP
- Poles : 02-20
- Material: Nylon 66 UL94V-0
- Pin Material: Brass /Tin-plated

Part No	Dimension (mm)	
	A	B
W2501V-02	2.50	7.50
W2501V-03	5.00	10.00
W2501V-04	7.50	12.50
W2501V-05	10.00	15.00
W2501V-06	12.50	17.50
W2501V-07	15.00	20.00
W2501V-08	17.50	22.50
W2501V-09	20.00	25.00
W2501V-10	22.50	27.50
W2501V-11	25.00	30.00
W2501V-12	27.50	32.50
W2501V-13	30.00	35.00
W2501V-14	32.50	37.50
W2501V-15	35.00	40.00
W2501V-16	37.50	42.50
W2501V-17	40.00	45.00
W2501V-18	42.50	47.50
W2501V-19	45.00	50.00
W2501V-20	47.50	52.50

X. ±0.30	APPD.	Mr.wu	TITLE:
XX ±0.20	CHKD:	Mr.wu	2.5间距 WAFER 4PIN 180°
XXX±0.05	DR:	Gus cheng	PART NO:
X' ±2"	UNITS:	mm	JIONS-0075
X' ±1"	SCALE:	1:1	SHEET:10/1

REVISION	DESCRIPTION	DATE
1	2014/03/17	

北京致恩启明电子科技有限公司	REV:
----------------	------