



使用温度范围 (Ambient temperature Range):	-25°~+85°
适用线规 (Applicable Wires):	AWG 22#~18#
适用基板厚度 (Applicable PCboard thickness):	1.6mm
额定电压 (Voltage rating):	250V AC,DC
额定电流 (Current rating):	5A
接触电阻 (Contact Resistance):	≤0.01Ω
绝缘电阻 (Insulation Resistance):	≥1000MΩ
耐压 (Withstand Voltage):	≥1000V/min

孔位	A	B
2	5.08	10.16
3	10.16	15.24
4	15.24	20.32
5	20.32	25.4
6	25.4	30.48
7	30.48	35.56
8	35.56	40.64
9	40.64	45.72
10	45.72	50.8
11	50.8	55.88
12	55.88	60.96
13	60.96	66.04
14	66.04	71.12
15	71.12	76.2

REV	ECN NO	DESCRIPTION	DATE
A	JIONS-0077		2012/01/16
1			

X. ±0.30	APPD: Mr.wu	TITLE:
.X ±0.20	CHKD: Mr.wu	5.08直针 板端 带靠背
.XX ±0.10		
.XXX ±0.05		
X' ±2"	DR: Gus chong	PART NO: JIONS-0077
X' ±1"		
UNITS: mm	SCALE: 1:1	SHEET: 10/1
北京致恩启明电子科技有限公司		REV: